

BOGE Type	Pressure		Effective Delivery Volume 50 Hz		Motor Power		Dimensions W × H × D mm	Weight kg
	bar	psig	m <sup>3</sup> /min	cfm	kW	PS		
S 61-3	8	116	7.85	277.2	45	60	2000 x 1065 x 1450	1180
S 61-3	10	145	7.1	250.7	45	60	2000 x 1065 x 1450	1180
S 61-3	13	189	6.03	212.9	45	60	2000 x 1065 x 1450	1180
S 75-3	8	116	9.88	348.9	55	75	2000 x 1065 x 1450	1260
S 75-3	10	145	8.9	314.3	55	75	2000 x 1065 x 1450	1260
S 75-3	13	189	7.45	263.1	55	75	2000 x 1065 x 1450	1260
S 90-3	8	116	11.35	400.8	65	90	2000 x 1065 x 1450	1328
S 90-3	10	145	10.18	359.5	65	90	2000 x 1065 x 1450	1328
S 90-3	13	189	8.87	313.2	65	90	2000 x 1065 x 1450	1328
S 100-3	8	116	12.8	452	75	100	2000 x 1065 x 1450	1358
S 100-3	10	145	11	388.5	75	100	2000 x 1065 x 1450	1358
S 100-3	13	189	9.53	336.5	75	100	2000 x 1065 x 1450	1358